

# MATERIAL SAFETY DATA SHEET

## SECTION 1 – PRODUCT INFORMATION

PRODUCT NAME: Roberts 3300 Max Performance + Premium M/P Carpet & Sheet Vinyl Adhesive  
 Roberts MSDS Code # 3300C  
 PRODUCT USES: For installing a wide variety of floorcovering materials

W.H.M.I.S. CLASSIFICATION: NON-CONTROLLED

V.O.C. CONTENT: As low as to be indeterminate

MANUFACTURER'S NAME: ROBERTS COMPANY CANADA LTD.

ADDRESS: 2070 Steeles Ave. Bramalea, Ontario L6T 1A7

24 HOUR (CANUTEC) PHONE: (613) 996-6666

## SECTION 2 – PREPARATION INFORMATION

PREPARED BY: Technical Dept.

INFORMATION PHONE: (905) 791-4444

SOURCES USED: Raw material supplier M.S.D.S.

DATE REVISED: September 25, 2009

## SECTION 3 - HAZARDOUS INGREDIENTS

COMPONENT	APPROX. %	UN#	CAS#	LD50	LC50
NO REPORTABLE INGREDIENTS					

## SECTION 4 – PHYSICAL DATA

BOILING POINT: 100° CFREEZING POINT: N/A

VAPOUR DENSITY (AIR=1): Heavier than air

VAPOUR PRESSURE (MM OF MERCURY): As for water.

SOLUBILITY IN WATER: Miscible

APPEARANCE AND ODOUR: Beige, soft buttery paste, very mild resinous odour.

SPECIFIC GRAVITY (H2O=1): 1.2 pH: 9 - 10

EVAPORATION RATE (BUTYL ACETATE=1): Slower

EVAPORATION RATE (ETHYL ACETATE=1): Slower

PERCENT VOLATILE: 28-31

ODOUR THRESHOLD (PPM): Not available

## SECTION 5 - FIRE AND EXPLOSION DATA

FLASHPOINT (specify method): None

METHOD USED:

IMPACT SENSITIVITY: Insensitive

FLAMMABLE LIMITS (% BY VOLUME):

LOWER: N/A UPPER: N/A

SENSITIVITY TO STATIC DISCHARGE: Insensitive

FIRE EXTINGUISHING MEDIA: Foam, CO2, Dry Chemical

AUTO IGNITION TEMP: N/A

TDG FLAMMABILITY CLASSIFICATION: Not regulated.

SPECIAL FIRE-FIGHTING PROCEDURES: Self-contained breathing apparatus should be worn for fires involving this product.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

## SECTION 6 - REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Excessive Heat

INCOMPATIBILITY (Materials to avoid): Strong oxidizers and caustics

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2, and Hydrocarbons upon combustion.

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: None

## SECTION 7 – TOXICOLOGICAL PROPERTIES

### ENTRY ROUTE TABLE

SKIN CONTACT	X	SKIN ABSORPTION		EYE CONTACT	X	INHALATION ACUTE		INHALATION CHRONIC		INGESTION	X
--------------	---	-----------------	--	-------------	---	------------------	--	--------------------	--	-----------	---

EFFECTS OF ACUTE EXPOSURE TO MATERIAL: Product may irritate eyes and skin. Ingestion causes vomiting, diarrhea, depressed respiration.

EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Skin chapping.

LD50 (SPECIFY SPECIES & ROUTE): Not available	LC50 (SPECIFY SPECIES): Not available	EXPOSURE LIMIT: Not available	IRRITANCY: None
SENSITIZING CAPACITY: None	CARCINOGENICITY: None	REPRODUCTIVITY EFFECTS: None	SYNERGISTIC MATERIALS: None known

## SECTION 8 – PREVENTATIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): None

VENTILATION: None should be required.

PROTECTIVE GLOVES: Impervious gloves if contact with adhesive likely

EYE PROTECTION: Goggles

OTHER PROTECTIVE EQUIPMENT: None required.

SPILL PROCEDURES: Mechanically collect. Wash area with water. Prevent from entering sewers or waterways. Spilled material may cause slippery conditions. Promptly report significant spills to appropriate authorities. Consult local regulations.

WASTE DISPOSAL METHOD: Destroy by incineration at an approved facility. Dried material only may be landfilled. Consult local regulations.

STORAGE & HANDLING PRECAUTIONS: Keep containers from excessive heat and freezing. Keep out of reach of children.

OTHER PRECAUTIONS: None.

## SECTION 9 – FIRST AID MEASURES

EYES: Flush with water for 20 minutes, holding eyelids open. Seek medical attention.

SKIN: Wash with soap and water. Seek medical attention if irritation develops.

INGESTION: Do not induce vomiting. If victim is conscious, give milk or water. Contact physician immediately.