

ALTROFIX W-39 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 07/17/2015

Version: 2.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: ALTROFIX W-39 A

Intended Use of the Product

Use of the Substance/Mixture: No use is specified.

Name, Address, and Telephone of the Responsible Party

Company

Altro Floors, Inc.
80 Industrial Way
Wilmington, MA 01887
978-657-6464

Emergency Telephone Number

Emergency Number : CHEMTREC 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Repr. 2 H361

Aquatic Acute 3 H402

Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Warning

Hazard Statements (GHS-US)

: H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H361 - Suspected of damaging fertility or the unborn child.
H402 - Harmful to aquatic life.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US)

: P261 - Avoid breathing vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear respiratory protection, eye protection, protective clothing, protective gloves.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

ALTROFIX W-39 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)
Bisphenol A-epichlorohydrin polymer	(CAS No) 25068-38-6	7 - 13
Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1), polymer with 1,3-diisocyanatomethylbenzene, nonylphenol-blocked (Polyurethane Prepolymer)	(CAS No) 102900-03-8	10 - 30
Alkyl (C12-14) glycidyl ether	(CAS No) 68609-97-2	1 - 5
Trimethylolpropane triacrylate	(CAS No) 15625-89-5	3 - 7
Propanol, oxybis-, dibenzoate	(CAS No) 27138-31-4	1 - 5
Phenol, 4-nonyl-, branched	(CAS No) 84852-15-3	0.5 - 1.5
Quartz*	(CAS No) 14808-60-7	0.1 - 1.0

*This product contains a material that may be hazardous when present as an airborne dust. Since this product is in a liquid form, the material is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with this material are not applicable to this product.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. Suspected of damaging fertility. Suspected of damaging the unborn child.

Inhalation: May cause respiratory irritation.

Skin Contact: Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Suspected of damaging fertility or the unborn child.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Potentially violent decomposition can occur above 350 °C.

Explosion Hazard: Product is not explosive but if hazardous polymerization occurs can have an oxidizing effect that could lead to fire and possible explosion.

Reactivity: Hazardous reactions are not expected to occur under normal conditions.

ALTROFIX W-39 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

Other Information: Refer to Section 9 for flammability properties.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing vapor, mist, or spray. Use only outdoors or in a well-ventilated area. Do not allow product to spread into the environment.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Place absorbed material in closed containers for disposal. Clean up spills immediately and dispose of waste safely. Notify authorities if product enters sewers or public waters.

Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: The substance will polymerize due to heating, on contact with peroxides, and under the influence of light. Heating may cause violent combustion or explosion producing acrid smoke. The substance may also spontaneously polymerize if it is not stabilized. Product to be handled in a closed system and under strictly controlled conditions.

Precautions for Safe Handling: Avoid contact with eyes, skin and clothing. Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Comply with applicable regulations.

Storage Conditions: Store in a dry, cool, and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures, and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Amines.

Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

ALTROFIX W-39 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Quartz (14808-60-7)		
Mexico	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen
USA OSHA	OSHA PEL (STEL) (mg/m ³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Nunavut	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass) 0.3 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass) 0.3 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	0.10 mg/m ³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction)
Yukon	OEL TWA (mg/m ³)	300 particle/mL

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure, but are not required. Product to be handled under strictly controlled conditions. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Thick liquid
Odor	: Not available
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: 32 °F
Boiling Point	: >= 425 °F (218 °C)

ALTROFIX W-39 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Flash Point	: > 200 °F (> 93 °C) (Tag Closed Cup or Setaflash method)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.46
Solubility	: Not available
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: 250,000 – 300,000 cps
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.
VOC	: <12 g/L

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions are not expected to occur under normal conditions.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

Incompatible Materials: strong acids. Strong bases. Strong oxidizers. Amines.

Hazardous Decomposition Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Suspected of damaging fertility or the unborn child.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg

ALTROFIX W-39 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Phenol, 4-nonyl-, branched (84852-15-3)	
LD50 Oral Rat	580 mg/kg
LD50 Dermal Rabbit	2031 mg/kg
Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Trimethylolpropane triacrylate (15625-89-5)	
LD50 Dermal Rabbit	5000 mg/kg
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
Trimethylolpropane triacrylate (15625-89-5)	
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LOEC (acute)	1 mg/l Daphnia magna
NOEC chronic crustacea	0.3 mg/l Daphnia magna
Phenol, 4-nonyl-, branched (84852-15-3)	
LC50 Fish 1	0.135 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	0.1351 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])

Persistence and Degradability

Bioaccumulative Potential

Phenol, 4-nonyl-, branched (84852-15-3)	
BCF Fish 1	271
Phenol (108-95-2)	
BCF Fish 1	(no significant bioaccumulation)
Log Pow	1.47

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT Not regulated for transport

In Accordance with IMDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(bisphenol A-(epichlorhydrin); epoxy resin)
Hazard Class : 9
Identification Number : UN3082

ALTROFIX W-39 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Packing Group : III
Label Codes : 9
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-F
Marine pollutant : Marine pollutant



In Accordance with IATA

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin)
Packing Group : III
Identification Number : UN3082
Hazard Class : 9
Label Codes : 9
ERG Code (IATA) : 9L



In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

SARA Section 311/312 Hazard Classes		Immediate (acute) health hazard Delayed (chronic) health hazard
Bisphenol A-epichlorohydrin polymer (25068-38-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Phenol, 4-nonyl-, branched (84852-15-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. S - S - indicates a substance that is identified in a proposed or final Significant New Uses Rule.	
SARA Section 313 - Emission Reporting	1.0 %	
Alkyl (C12-14) glycidyl ether (68609-97-2)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
Propanol, oxybis-, dibenzoate (27138-31-4)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Quartz (14808-60-7)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard	
Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1), polymer with 1,3-diisocyanatomethylbenzene, nonylphenol-blocked (102900-03-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Trimethylolpropane triacrylate (15625-89-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

US State Regulations

Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

ALTROFIX W-39 A

Safety Data Sheet


According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Canadian Regulations

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---



Phenol, 4-nonyl-, branched (84852-15-3)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Alkyl (C12-14) glycidyl ether (68609-97-2)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Propanol, oxybis-, dibenzoate (27138-31-4)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1), polymer with 1,3-diisocyanatomethylbenzene, nonylphenol-blocked (102900-03-8)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Trimethylolpropane triacrylate (15625-89-5)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 07/17/2015
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H361	Suspected of damaging fertility or the unborn child
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects

ALTROFIX W-39 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Party Responsible for the Preparation of This Document

Altro Floors, Inc.
80 Industrial Way
Wilmington, MA 01887
978-657-6464

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2